

YT-760B semi-auto handfree barcode scanner with laser rugged stand with USB cable

Wireless Transmitting Distance (without barrier) ——

Infrared induction distance 150 - 200mm

Optical Source 650nm Visible red light diode

Image Resolution ≥ 4 mil

Minimum Contrast $\geq 30\%$

Barcode Types "UPC/EAN/JAN,UPC/EAN with supplementals"

UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII,

Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93,

Discrete 2 of 5 IATA,RSSvarians,Codabar,chinese 2 of 5,Interleaved 2/5,

Interleaved 2 of 5, International general dimensional barcodes"

Decoding Speed 100times/s

Barcode Sensitivity Tilt $\pm 65^\circ$

Rotate $\pm 42^\circ$

Deflection $\pm 60^\circ$

Data Interface Port RJ-45

Mechanical and Electric Performance

Size(Length x Width x Height) 92.5×70×154.6 mm

Weight (except cable) 148g

Indicator Siren and LED light

Battery Capacity ——

Max.Power 500mw

Working Voltage DC5V

Current Max.Curren 100ma

Working Current 97ma

Stand-by Current 77ma

Sleeping Current ——

Charging Current 450ma

Accessory List

Data line USB data line(1.8m)

RS232 data line(1.8m)

Receiver ——

Drive CD ——

Operation Manual 1 Piece

Charging Cradle ——

Stand 1 Set

Environmental Parameter

Storage Temperature $-40^\circ\text{C} \sim 60^\circ\text{C}$

Working Temperature $0^\circ\text{C} \sim 50^\circ\text{C}$

Relative Humidity 0 ~ 95%

Height Range 1.5m

IP Rating IP52

Certificates:

CE,RoHS,EMC,LVD□ISO9001:2008□ISO14001:2004



