

YT-760B semi-auto handfree barcode scanner with laser rugged stand with USB cable

Wireless Transmitting Distance (without barrier) ——

Infrared induction distance 150 - 200mm

Optical Source 650nm Visible red light diode

Image Resolution  $\geq 4\text{mil}$

Minimum Contrast  $\geq 30\%$

Barcode Types "UPC/EAN/JAN, UPC/EAN with supplementals

UCC/EAN128, Code39, MSI, Code11, Code39 Full ASCII,

Code39 Trioptic, Code128, Code128 Full ASCII Codabar, Code93,

Discrete 2 of 5 IATA, RSS variants, Codabar, Chinese 2 of 5, Interleaved 2/5,

Interleaved 2 of 5, International general dimensional barcodes"

Decoding Speed 100times/s

Barcode Sensitivity Tilt  $\pm 65^\circ$

Rotate  $\pm 42^\circ$

Deflection  $\pm 60^\circ$

Data Interface Port RJ-45

Mechanical and Electric Performance

Size (Length x Width x Height) 92.5x70x154.6 mm

Weight (except cable) 148g

Indicator Siren and LED light

Battery Capacity ——

Max. Power 500mw

Working Voltage DC5V

Current Max. Current 100ma

Working Current 97ma

Stand-by Current 77ma

Sleeping Current ——

Charging Current 450ma

Accessory List

Data line USB data line (1.8m)

RS232 data line (1.8m)

Receiver ——

Drive CD ——

Operation Manual 1 Piece

Charging Cradle ——

Stand 1 Set

Environmental Parameter

Storage Temperature  $-40^\circ\text{C} \sim 60^\circ\text{C}$

Working Temperature  $0^\circ\text{C} \sim 50^\circ\text{C}$

Relative Humidity 0 ~ 95%

Height Range 1.5m

IP Rating IP52

Certificates:

CE, RoHS, EMC, LVD, ISO9001:2008, ISO14001:2004



