

The cheapest Laser Wired Barcode 3d Gun/Scanner Brand Yumite YT-760L portable ultrasound scanner

Easy Using  
Easy Setting  
Plug and Play

We are the barcode scanner factory located in shenzhen,china. We can provide various kinds of barcode scanner.

Such as: wireless/wired laser barcode scanner, wireless/wired CCD barcode scanner, scanner mouldle, Bluetooth barcode scanner, 2.4G/433MHz barcode scanner, 2D barcode scanner, Omnidirectional barcode scanner.

There are 7 seasoned hardware and software engineer in our research department and our factory director have 20 years working experience in the barcode scanner industry. Depend on the strong research ability, all of the Scanning engine and decoding software is developed by ourself.

We sincerely hope we will have nice cooperation and work together to create a brilliant future!

Wireless Transmitting Distanc (without barrier) ——

Infrared induction distance ——

Optical Source 650nm Visible red light diode

Image Resolution  $\geq 4\text{mil}$

Minimum Contrast  $\geq 30\%$

Barcode Types "UPC/EAN/JAN,UPC/EAN with supplementals□

UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII,

Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93,

Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5,

Interleaved 2 of 5, International general dimensional barcodes□"

Decoding Speed 100times/s

Barcode Sensitivity Tilt  $\pm 65^\circ$

Rotate  $\pm 42^\circ$

Deflection  $\pm 60^\circ$

Data Interface Port RJ-45

Mechanical and Electric Performance

Size(Length x Width x Height) 156×64×91 mm

Weight (except cable) 108g

Indicator Siren and LED light

Battery Capacity ——

Max.Power 450mw

Working Voltage DC5V

Current Max.Curren 90ma

Working Current 62ma

Stand-by Current 71ma

Sleeping Current ——

Charging Current 450ma

Accessory List

Data line USB data line(1.8m)

Receiver ——

Drive CD ——  
Operation Manual 1 Piece  
Charging Cradle ——  
Environmental Parameter  
Storage Temperature -40°C ~ 60°C  
Working Temperature 0°C ~ 50°C  
Relative Humidity 0 ~ 95%  
Height Range 1.5m  
IP Rating: IP52

Certificates:  
CE,RoHS,EMC,LVD□ISO9001:2008□ISO14001:2004











