#### **Features**

Bluetooth wireless technology and unique bluetooth solution

Easy match code

Better drop-resistance

Uesed for PC, mobile phone, tablet

Fast speed 100times/second

One to One pairing, easy setting

Flicking Scanning and Auto Scanning and Continuous Scanning

Large capacity 8MB, equal to save more than 300000 bar codes

Longer transmitting distance 20M

Supporting customization

Fully plug&play compliant

## **Applications**

Supermarket, Retail, Healthcare, Logistics, Postal Communication, Government, Clothing industry, Power Industry, Hospital, Bookstore, School

Wireless Transmitting Distanc (without

barrier)

15 - 20m

Infrared induction distance

Optical Source 650nm Visible red light diode

Image Resolution ≥4mil

Minimum Contrast ≥ 30%

UPC/EAN/JAN, UPC/EAN with supplementals,

UCC/EAN128, Code39, MSI, Code11, Code39 Full ASCII,

Code39 Trioptic, Code128, Code128 Full ASCII

Codabar, Code 93,

Barcode Types

Discrete 2 of 5 IATA, RSS vanrians, Codabar, chinese 2 of

5.Interleaved 2/5.

Interleaved 2 of 5, International general dimensional

barcodes.

Decoding Speed 100times/s

Barcode Sensitivity Rotate ±42°

Deflection ±60°

Data Interface Port RJ-45

### Mechanical and Electric Performance

Size(Length x Width x Height) 92.5×70×154.6 mm

Weight (except cable) 168g

Indicator Siren and LED light

Battery Capacity 600mah

Max.Power 350mw

Working Voltage DC5V

Max.Curren 70ma

Working Current 66ma Current

Stand-by Current 45ma

Sleeping Current ≤ 2ua

Charging Current 450ma

### Accessory List

USB data line(1m)
Data line

--

Receiver 1Piece

Drive CD 1Piece

Operation Manual 1Piece

Charging Cradle --

#### **Environmental Parameter**

Storage Temperature  $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ 

Working Temperature  $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ 

Relative Humidity  $0 \sim 95\%$ 

Height Range 1.5m

IP Rating IP52

# Certificates

CE,RoHS,EMC,LVD,ISO9001:2008,ISO14001:2004

