

ccd barcode scanner head,ccd barcode reader head,mini barcode scanner ER20 is designed for a handheld barcode scanner or barcode scanner module use.

Support interface customization and easily read all 1d barcode.

Drop resistance and able to read modile and tablet pc barcode.



Imaging Sensor		ССР
Resolution Ratio		2500 pixel
Image Resolution		≥ 5mil
Minimum Contrast		≥ 30%
Barcode Types		Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar etc.
Decoding Speed		280times/s
Barcode Sensitivity	Tilt	±55°
	Rotate	±25°
	Deflection	±75°
Data Interface Port		FPC flat cable separation distance: 12*0.5mm
Mechanical and Electri	c Performance	
Size(Length x Width x Height)		33.7×25.8×9.9mm
Weight (except cable)		9g
Indicator		buzzer and LED light
Max.Power		400mw
Working Voltage		DC5V
Current	Max.Current	80ma
	Working Current	74ma
	Stand-by Current	24ma
	Sleeping Current	
Accessory List		
Data line		USB data line
		RS232 data line
Environmental Parame	ter	
Storage Temperature		-40°C ~ 60°C
Working Temperature		0°C ~ 50°C
Relative Humidity		0 ~ 95%







