competitive price induction barcode scanner with stand





Auto-sense wired laser barcode scanner YT-760A can be connected with POS systems and very convenient to use.



Auto-

sense wired laser barcode scanner YT-760A is very easy to use, only need to put the scanne r in the stand and then it read the barcode by itself.



	Model	YT-760A
		Image
lmage		
		Performance Parameter
Depth Filed		20mm EANI3(10mil,13loytes)250mm 15min coole39(10mil,6loytes) 260mm 15min coole39(15.6mil,6bytes) 350mm coole128(10mil,6loytes) 270mm 20min 20min EANI3(15.6mil,6loytes) 330mm EANI3(15.6mil,13loytes) 360mm 0 100 200 300 400
Wireless Trans (without barrier	smitting Distance	
Infrared inducti	2	150 - 200mm
Optical Source	1)	650nm Visible red light diode
Reading Percision		≥4mil
	root	
Minimum Conti	No. State of the S	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal
Minimum Conti	acity	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second
Minimum Control Decoding Capa Decoding Spec	acity ed Tilt	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65°
Minimum Control Decoding Capa Decoding Specification	acity ed Tilt Rotate	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second
Minimum Control Decoding Capa Decoding Specification Barcode Sensitivity	acity ed Tilt	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface	acity ed Tilt Rotate Deflection	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface	acity ed Tilt Rotate	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x 1) Weight	acity ed Tilt Rotate Deflection	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g
Decoding Capa Decoding Specific Specif	ed Trilt Rotate Deflection Width x Height)	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm
Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	acity ed Tilt Rotate Deflection Width x Height)	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw
Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	acity ed Tilt Rotate Deflection Width x Height)	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to the second to the	acity ed Tilt Rotate Deflection Width x Height)	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw
Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma ——
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to the second	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Current Data Cable Wireless Rece	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List
Decoding Capa Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Heidicator Battery Capaci Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB —— —— —— ———————————————————————————
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x to the sensitivity Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD Operation Man	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ———
Decoding Capa Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Heidicator Battery Capaci Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ————————————————————————————————————
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Standby Curent ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95%
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x Very Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Temper Relative Humic Heigth Range	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ———— 1Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% 1.5M
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95%

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:

Approval Date: 2s Dec. 2014 Expiry Date: 25 Dec. 2017

For Supple Supple Supplement Supp

Section to inspection of

And not desirate the control of the Analysis I

The contribute information can be desirate in the CNA nations (MMNCNA CONCNA) in collection of the contribute also be desirated through the contribute can be desirated through the contribute can be desirated to the contribute to early valid when can be desirated to early the contribute to early valid when contributed to early the contribute to early the contribute and the contribute to early the contribute and the contribute a

CAS

CERTIFICATE OF REGISTRATION

Certificate No. . 117 14 £1 0796 805 This is to certify the environmental management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Ximgqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6E, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Boosen District, Shenzhen

Signed by:

Dogwood

Expery Date: 25 the: 20

Manghe Super (authority framework for 1 for a bidge)

Citical Super (authority between the control of authority (bidge))

Citical Super (bidge)

in white

Not continued the first by the boundaries

Rike Steam Mingles (New York)

6 6

The correlative substructions can be played on the CNA another WITH, CNA, ALM, b). The unbidome of the criticism and the Withard Effective service services to be played as the control of the control of the service services. The control of the service services are unbidom to service services and service services are controlled to service services are controlled to services and services are controlled to services and the controlled are controlled to services and the controlled are controlled to service and the controlled are controlled as and the controlled are controlled to the controlled are controlled as and the controlled are controlled as a service to the controlled are controlled as a controlled as a service to the controlled are controlled as a service to the controlled as a service to the controlled are controlled as a service to the controlled are controlled as a service to the controlled as a service to the controlled are controlled as a service to the controlled as a serv



Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsieng Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bear an District, Sherathen Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bear an District, Sherathen Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-41200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.



RoHS





EC-R&TTE Certificate

Certificate Number: UNIZEL4122403EC-1

Applicant

Shenzhen World Reputation Electronics Technology Co., Ltd.
5F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Shenzhen World Reputations Electronics Technology Co., Ltd.
6F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Bar-code Scanner
Vivorite

Y1-1300, YT-850, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art.3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 480-1/-3	UNI2014122403ER-1	Pass
A432	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

with the council #ATTE directive 90/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

Date of issue



americaned United Leading Leaflinghopy of Rober 317-376 Block 1, University Tean Februsiagy 5° Zens, South Section, Honghuaing Industrial Paix, Nanhan Denki, Shenstein, PM, 51809 Na - 98, 756-8010090 Fax +98-755-98180138 Na - 98-756-8010090 Exa +98-755-98180138 Description and 98-75









企业文化 Corporate culture

企业愿景 Corporate vision

成为一家深受社会尊敬的企业 To be one well-beloved enterprise by our society.

企业价值 Corporate value

以科技创新优化人类生活品质 To optimize the life quality for human being by our technical innovation.

企业理念 Corporate philosophy

执行高效团结,坚持拼搏共赢 To carry out efficient unity, insist struggle and win-win.

企业品格 Corporate moral

责任、忠诚、感恩、分享 Responsible,loyal,grateful and share.

企业精神 Corporate spirit

历经千辛万苦 Go through innumerable trials and hardships.