Handheld wireless 433Mhz 1D laser barcode scanner with USB interface and big memory



Description



Yumite barcode scanner YT-884 is Handheld wireless 433Mhz 1D laser barcode scanner with USB

interface and big memory. The latest technical accomplishment is applied to the engine and decoding

function, reading codes better and faster than the similar in the market.

YT-884 can work continuously for 8hours when fully charged and the storage is very big for more than 300,000 data. also it can receive the data from 400m distance in the open area. in addition , when it out off the receiving range , the scanner will turn into storage mode by itself so the data won't

be lost.

Feature



- Wireless Cordless Handheld Bar Code Scanner
- 32-bit Decoder, Anti-interference, Mobile Moveable, Optical Laser, USB Optional, Long-Range
- USB Rechargeable bar code reader, with mini USB receiver, USB cable, Plug and Play

Specification



imitting Distance on distance	Image Im				
) on distance ion	20mm EAN13(10mil.13bytes)250mm 20mm coole39(10mil.6bytes) 260mm 15mm coole39(10mil.6bytes) 350mm 15mm coole39(15.6mil.6bytes) 350mm 15mm coole128(15.6mil.6bytes) 350mm 20mm coole128(15.6mil.6bytes) 330mm 30mm EAN13(15.6mil.13bytes) 360mm 0 100 200 300 300 - 400M G50nm Visible red light diode				
) on distance ion	20mm EAN13(10mil.,13bytes)250mm 15mm coole39(10mil.,6bytes) 260mm 15mm coole39(15.6mil.,6bytes) 250mm 15mm coole128(15.6mil.,6bytes) 350mm 15mm coole128(15.6mil.,6bytes) 350mm 20mm coole128(15.6mil.,6bytes) 330mm 20mm coole128(15.6mil.,6bytes) 330mm 20mm coole128(15.6mil.,13bytes) 360mm 30mn EAN13(15.6mil.,13bytes) 360mm 0 100 200 300 400 300 - 400M 650nm Visible red light diode				
) on distance ion	650nm Visible red light diode				
on distance					
	>4mil				
ast	≥ 30%				
city	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.				
d	100times/second				
Tilt	±65°				
Rotate	±42°				
Defiection	±60° RJ-45				
	Mechanical and Electric Performance				
Vidth XHeight)	92.5×70×154.6 mm				
succession and succes	162g				
	Siren and LED light				
tery Capacity 600mah x.Power 345mw					
e	DC5V				
Max.Current	85ma				
Working Curent	83ma				
	60ma				
	≤ 60ua 450ma				
	Accessory List				
	Micro USB				
ta canle					
ver	433MHZ				
Jal	1				
5.310 					
	Environmental Parameter				
rature	-40°C ~ 60°C				
	0°C ~ 50°C				
цу	0 ~ 95% 1.5M				
t Range 1.5M ting IP52					
	Rotate Deflection //idth XHeight) / / / / / / / / / / / / / / / / / / /				

Certification

Yumite



	l <u>LN</u>				
Certificate	8	EC-R&TTE Certificate			
Compliance	Applicant	4	Shenzhen World Reputation Elect	Certificate Number: UN	H.
Certificate Number: UNI28141214038C-3 Applicant Shenzhen World Reputation Electronics Technology Co., Ltd. Ef. B Building, B Avas, Xrogsing Buuness Building, No.1, Dezheng Road, Shiong Community, Shyan, Bara Dubrict, Shenzhen Product Ber-code Scanner Trade Name Yumite NN Yumite NN	Manufactur Product Trade Namu MIN	H 1	6F. B Building, B Area, Xinggiang B, Shilong Community, Shiyan, Bao'an Shenzhen World Reputation Elsect 6F. B Building, B Area, Xinggiang B, Shilong Community, Shiyan, Bao'an Ban-code Scanner Yumitie	Bluding, B. Area, Xingquang Business Building, No. 1, Dezheng Road, ong Community, Shiyan, Bao'an Diatrict, Shenzhen nzhen World Reputation Electronics Technology Co., Ltd. B Sluding, B. Area, Xingquang Business Building, No. 1, Dezheng Road, orde Scammunity, Shiyan, Bao'an Dietrict, Shenzhen orde Scammer, Statum, Statum, Statum, Statum, Statum, Statum, Italia, V. 1990, VT-1900, VT-1900, VT-2200, VT-2200, VT-240, VT-380, VT-1980, VT-1200, VT-1400, VT-1500, VT-2200, VT-240, VT-380, VT-1980, VT-1800, VT-1800, VT-2200, VT-240, VT-380, VT-1800, VT-1800, VT-1800, VT-2200, VT-240, VT-380, VT-1800, VT-1800, VT-1800, VT-2200, VT-240, VT-380, VT-1800, VT-1800, VT-1800, VT-2200, VT-240, VT-380, VT-200, VT-1800, VT-1800, VT-2200, VT-240, VT-380, VT-200, VT-1800, VT-1800, VT-2200, VT-240, VT-380, VT-2200, VT-380, VT-380, VT-2200, VT-240, VT-380, VT-280, VT-2200, VT-380, VT-240, VT-380, VT-2	
M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-3100B, YT- M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX	Essential n	-	Appled Specifications/Standards	Documentary Evidence	Result
na na sete de la compansión	Art.3.1(a)	Heath	Not assessed		
Test Standard: IEC62321:2013	A13.1(R)	Safety	EN60950-1	UNI20141224035R-1	Pass
92	Art.3.1(b) Art.3.2	EMC Radio	ETSI EN301 480-1/-3 ETSI EN300 440	UNI2014122403ER-1 UNI2014122403ER-2	Pass
RoHS Devotive 2011/MSEU. It is only valid in connection with the test report number: UNI2014122403RR-3.	with the co compliance	with this D	ove has been tested by us with the II E directive \$955°EC. It is possible to u inective. In relates to the submitted documents	se CE marking to demonst	
And the second s	Room 317-319 5° Zone, South Nanshan Date	united Te Disch 1. Sin Section. No 3. Streicher	Attention of the second	C	E 認識
Number Parent Resident PDP Arents				C. A. S. A.	122

Our factory





