small size wired usb ccd barcode moudle



Description

The CCD scan engine can decode nearly any kinds of 1D (striped) barcode in your project usi ng this

adorable compact barcode scanner. We've looked all over for a small, light, lowpower scanne r module that can be easily integrated. This OEM ccd scanner engine can easily integrated int o various Kiosks, ticketing machines, ATM, PDA, POS etc. Or connect with Android/ Iphone to scan directly.



The YT-

M301 CCD scan engine is all in one scanner module which is the simplest we could find.

On the end is just a USB cable, plug it into any computer and start to decode within one seco nd.

This QR scanner supports RS232 and USB interface socket. More interface requirements are n egotiable.



Image	Para	Model	YT-M301	
Depth Filed 30m code/39(10)(4,6yrtes) 3(30m) 99m code/39(10)(4,6yrtes) 3(30m) 430m) 99m code/39(10)(4,6yrtes) 3(30m) 450m) 30m code/39(10)(4,6yrtes) 3(30m) 450m) 40m EAR(3)(1,5yrtes) 3(30m) 430m) 90m code/39(10)(4,6yrtes) 3(30m) 430m) 90m EAR(3)(1,5yrtes) 3(30m) 430m) 90m Code(30,13yrtes) 3(30m) 430m) 90m EAR(3)(1,5yrtes) 3(30m) 430m) 90m Code(30,13yrtes) 3(30m) 430m) 90m Code(20,13yrtes) 3(30m) 430m) 90m Code(20,13yrtes) 3(30m) 500 90m Code(30	Image			
apprint Na 30nn code 39(156nl,6bytes) 420nn 90nn code 128(156nl,6bytes) 430nn 40nn code 128(156nl,6bytes) 430nn 90nn EAN13(106.1300tes) 430nn 0 100 200 300 400 90nn EAN13(156.nl,5bytes) 430nn 400n 100 200 300 400 500 Wireless Transmitting Distance (without barrier) — Infrared induction distance 0 100 200 300 400 500 Poptical Source 620nm Visible red light diode Image Resolution 2500Pixel Reading Precision 2 5mil Minimum Contrast ≥ 30% Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codebar, Interleaved 2 of 5, IS5N, Code 90, UCC/EAN-128, GS1 Databar, ect.	Performance Parameter			
(without barrier) ———————————— Infrared induction distance 150 - 200mm Optical Source 620nm Visible red light diode Imaging Sensor CCD Imaging Sensor CCD Reading Precision 2 50mil Minimum Contrast 2 30% Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Titl Rate ±25° Rotate ±25° Data Interface micro usb Mechanical and Electric! Performance Size(Length x Width x Height) 50×37.3×21.7 mm Weight 27g Indicator Siren and LED light Battery Capacity ——— Max.Power 700mw Working Voltage DCSV Current Max.Current Variange Decestre ——— Charging Current ——— Accessory List Dota Data Cable Micro USB <t< td=""><td colspan="2">Depth Filed</td><td>32mm code39(15.6mil,6bytes) 420mm 90mm code128(10mil,6bytes) 340mm 32mm code128(10mil,6bytes) 340mm 40mm code128(15.6mil,6bytes) 450mm 30mm EANI3(10mil,13bytes) 310mm 80mm EANI3(15.6mil,13bytes) 430mm</td></t<>	Depth Filed		32mm code39(15.6mil,6bytes) 420mm 90mm code128(10mil,6bytes) 340mm 32mm code128(10mil,6bytes) 340mm 40mm code128(15.6mil,6bytes) 450mm 30mm EANI3(10mil,13bytes) 310mm 80mm EANI3(15.6mil,13bytes) 430mm	
Infrared induction distance 150 - 200mm Optical Source 620mm Visible red light diode Image Resolution 2500Pixel Reading Precision ≥ 5mil Minimum Contrast ≥ 30% Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 39, UPC-A, UPC-E, Codabar, Decoding Speed 280times/second Barcode Tilt ± 455° Rotate ± 25° Deflection ± 75° Data Interface micro usb Mechanical and Electric! Performance Size(Length x Width x Height) 50×37,3×21,7 mm Weight 27g Indicator Siren and LED light Battery Capacity Max.Current 140ma Working Voltage DcS5V Max.Current 45ma Standby Current Standby Current Standby Current Max.Current Standby Current Operation Manual 1 C				
Optical Source 620nm Visible red light diode Image Resolution 2500Pixel Reading Precision ≥ 5mil Minimum Contrast ≥ 30% Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UPC-A, UPC-E, Codabar, ed. Decoding Speed 280times/second Barcode 11t Barcode 11t Barcode 280times/second Barcode 280times/second Barcode 275° Deflection ±75° Minimum Constrate micro usb Mechanical and Electric! Performance Size(Length x Width x Height) Solar of Siren and LED light Battery Capacity Max.Power 700mw Working Current 90ma Standby Current 40ma Sileeping Current Current Micro USB Sileeping Current Charge Station 1 <td colspan="2"></td> <td>150 - 200mm</td>			150 - 200mm	
Imaging Sensor CCD Image Resolution 2500Pixel Reading Precision ≥ 5mil Minimum Contrast ≥ 30% Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Tilt Rotate ±25° Deflection ±75° Data Interface micro usb Mechanical and Electricl Performance Size(Length x Width x Height) Size(Length x Width x Height) 50×37.3×21.7 mm Weight 27g Indicator Siren and LED light Battroy Capacity Max.Power 700mw Working Voltage DCSV Working Current 90ma Standby Current 90ma Standby Current Max Courent 45ma Standby Current Micro USB Micro USB Oberation Manual 1 Charges Temperature Corrent				
Reading Precision ≥ 5mil Minimum Contrast ≥ 30% Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Barcode Sensitivity Till ±55° Data Interface micro usb Data Interface micro usb Mechanical and Electric! Performance Size(Length x Width x Height) 50×37.3×21.7 mm Weight 27g Indicator Siren and LED light Battery Capacity —— Max.Power 700mw Working Voltage DC5V Working Current 40ma Standby Current 90ma Standby Current 90ma Standby Current 45ma Standby Current —— Micro USB —— Micro USB —— Micro USB —— Charging Current —— Standby Current —— Standby Current —— Operation Manual 1 Charging Current	Imaging Sensor		CCD	
Minimum Contrast ≥ 30% Decoding Capacity Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Sped 280times/second Barcode Sensitivity Titt 455° Data Interface micro usb Mechanical and Electric! Performance Size(Length x Width x Height) 50×37.3×21.7 mm Weight 27g Indicator Siren and LED light Battery Capacity —— Max.Power 700mw Working Voltage DCSV Working Voltage DCSV Current 140ma Working Current 90ma Standby Current 90ma Standby Current —— Charging Current —— Accessory List —— Data colse —— Wireless Receiver —— CD —— CD —— CD —— CD —— CD —— Charge Station —— CD —— CD —— Charge Station —— CD —— CD —— CD				
Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Sensitivity Tilt ±55° Data Interface micro usb Mechanical and Electricl Performance Size(Length x Width x Height) Size(Length x Width x Height) Wichart Siren and LED light Battery Capacity Current Adx.Current Max.Power 700mw Working Voltage DC5V Working Current 90ma Standby Current 45ma Sleeping Current Accessory List Data Cable Enironmental Parameter Storage Temperature Advice ~ 60°C Working Temperature Or Enironmental Parameter Storage Temperature Advice ~ 60°C Wireless Receiver				
Barcode Sensitivity Tilt Rotate ±55° Data Interface			Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar,	
Barcode Sensitivity Rotate ±25° Deflection ±75° Data Interface micro usb Mechanical and Electricl Performance Size(Length x Width x Height) Size(Length x Width x Height) Size(Length x Width x Height) Wechanical and Electricl Performance Size(Length x Width x Height) Size(Length x Height) Size(Length x Width x Height) Mechanical and Electricl Performance Size(Length x Height) Max.Ower Conver Max.Ower Current Max.Current Micro USB Current Current Micro USB Current Micro USB Current	Decoding Speed		280times/second	
Sensitivity Notate Deflection 125° (Deflection Data Interface micro usb Mechanical and Electricl Performance Size(Length x Width x Height) Size(Length x Width x Height) 50×37.3×21.7 mm Weight 27g Indicator Siren and LED light Battery Capacity —— Max.Power 700mw Working Voltage DC5V Max.Current 140ma Working Current 90ma Steeping Current 90ma Steeping Current —— Accessory List Data Cable Micro USB Output —— Conduct —— Conduct —— Conduct —— Environmental Parameter Conduct —— Environmental Parameter Storage Temperature <				
Data Interface micro usb Mechanical and Electricl Performance Size(Length x Width x Height) 50×37.3×21.7 mm Weight 27g Indicator Siren and LED light Battery Capacity —— Max.Power 700mw Working Voltage DC5V Max.Current 140ma Working Voltage 90ma Current Working Current Max.Current 45ma Standby Current —— Charging Current —— Standby Current —— Accessory List —— Micro USB —— Operation Manual 1 Charge Temperature —— Storage Temperature 40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IPS2	Sensitivity			
Mechanical and Electricl Performance Size(Length x Width x Height) 50×37.3×21.7 mm Weight 27g Indicator Siren and LED light Battery Capacity —— Max.Power 700mw Working Voltage DC5V Current 140ma Working Current 90ma Standby Current 90ma Sleeping Current —— Charging Current —— Data Cable Micro USB Wireless Receiver —— CD —— Operation Manual 1 Charge Station —— Storage Temperature 40°C ~ 60°C Working Temperature 0° ~ 95% Height Range 1.5M IP Rating IP52		Scheouon		
Weight 27g Indicator Siren and LED light Battery Capacity Max.Power 700mw Working Voltage DC5V Current Max.Current Working Current 90ma Standby Current 90ma Steleping Current 90ma Standby Current 45ma Sleeping Current Charging Current Micro USB Operation Manual 1 Charge Station Storage Temperature Storage Temperature Working Temperature 0°°C Working Temperature 0°°C Height Range 1.5M IP Rating IP52				
Indicator Siren and LED light Battery Capacity —— Max.Power 700mw Working Voltage DC5V Current Max.Current Working Current 90ma Standby Current 90ma Steeping Current 45ma Sleeping Current —— Charging Current —— Standby Current —— Standby Current —— Standby Current —— Charging Current —— Data Cable Micro USB Operation Manual 1 Charge Station —— Enironmental Parameter Storage Temperature 40°C ~ 60°C Working Temperature 0° ~ 95% Height Range 1.5M IP Rating IP52	Size(Length x Width x Height)		50×37.3×21.7 mm	
Battery Capacity Max.Power 700mw Working Voltage DC5V Current Max.Current Working Current 90ma Standby Current 90ma Steeping Current 90ma Sleeping Current Charging Current Sleeping Current Accessory List Data Cable Micro USB Wireless Receiver CD Operation Manual 1 Charge Station Enironmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52	Weight		27g	
Max.Power 700mw Working Voltage DC5V Current Max.Current Working Current 90ma Standby Current 90ma Standby Current 45ma Steeping Current Charging Current Charging Current Accessory List Data Cable Micro USB Wireless Receiver CD Operation Manual 1 Charge Station Enironmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0° 25% Height Range 1.5M IP Rating IP52	Indicator		Siren and LED light	
Working Voltage DC5V Rurent 140ma Working Current 90ma Standby Current 90ma Stepping Current 45ma Sleeping Current Charging Current Charging Current Charging Current Charging Current Data Cable Micro USB Data Cable Wireless Receiver CD Operation Manual 1 Charge Station Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52				
Max.Current 140ma Working Current 90ma Standby Current 90ma Steeping Current 45ma Sleeping Current —— Charging Current —— Charging Current —— Charging Current —— Charging Current —— Data Cable Micro USB Wireless Receiver —— CD —— Operation Manual 1 Charge Station —— Enironmental Parameter Storage Temperature Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0° ~ 95% Height Range 1.5M IP Rating IP52				
Working Current 90ma Standby Current 45ma Steeping Current Charging Current Charging Current Charging Current Accessory List Data Cable Wireless Receiver CD Operation Manual 1 Charge Temperature Storage Temperature Working Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Working Temperature 1.5M Height Range 1.5M IP Rating IP52				
Standby Current 45ma Sleeping Current Charging Current Accessory List Data Cable Micro USB Operation Manual CD Operation Manual 1 Charge Station Storage Temperature Working Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52				
Charging Current Accessory List Data Cable Micro USB Wireless Receiver CD Operation Manual 1 Charge Station Enironmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52	Current	Standby Current		
Accessory List Data Cable Micro USB Wireless Receiver —— CD —— Operation Manual 1 Charge Station —— Enironmental Parameter Storage Temperature Vorking Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52			,	
Micro USB Data Cable —— Wireless Receiver —— CD —— Operation Manual 1 Charge Station —— Enironmental Parameter Storage Temperature Vorking Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0° ~ 95% Height Range 1.5M IP Rating IP52				
Image: CD Image: CD Operation Manual 1 Charge Station Enironmental Parameter Storage Temperature O°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52	Data Cable			
CD Operation Manual 1 Charge Station Enironmental Parameter Storage Temperature Working Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52				
Operation Manual 1 Charge Station Enironmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52		ver		
Charge Station —— Enironmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52		al	• · · · · · · · · · · · · · · · · · · ·	
Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52				
Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52	<u> </u>			
Relative Humidity 0 ~ 95% Height Range 1.5M IP Rating IP52				
Height Range 1.5M IP Rating IP52				
IP Rating IP52				
Certification			IP52	
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004			Certification	



welcome to contact with us!