wireless Bluetooth laser barcode reader



The bluetooth laser barcode scanner is easy for using. It can be paired with your device which is with bluetooth, no more software.YT-890 support ios, Mac, Android, smart phone,PDA and so on.

Performance Parameter Performance Parameter	Para Model	YT-890
Performance Parameter Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed De		Image
Depth Filed Septh Filed S	lmage	Name of the state
Mithout barrier	Depth Filed	20mm EAN13(10mil,13bytes)250mm 15mm
Without barrier	Wireless Transmitting Distance	15 - 20M
Detail Source Seading Precision ≥ 4mil ≥ 30%	(Without barrier)	15 (2011)
Decoding Precision 2 4mil 2 30%		GEOrges Visible and light dind
Second content	~ 	
UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39, MSI, Code11,Code39 Full ASCII, Code39 Troptic, Code128, Code128 Full ASCII, Code39, Troptic, Code37 Full ASCII, Code39, Troptic, Code37 Full ASCII, Code39, Troptic, Code128, Code128, Code128, Code128, Code128, Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5, Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.		No. Park Company Compa
Tilt	Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal
Totate	Decoding Speed	
Content		
Deletion State S	Soneitivity	
Mechanical and Electric Performance	Deflection	10,400,000
Size (Length x Width x Height) 92.5×70×154.6 mm		
Veight 168g	Size(Length x Width x Height)	
### Size and LED light ### S		STROMEN.
## Startery Capacity ## G00mah Max. Power		-
Max. Power 350mw		
Max. Current Max. Current Toma Working Current Standby Current 45ma	The state of the s	
Current 70ma Working Current 66ma Standby Current 45ma Sleeping Current 450ma Charging Current Accessory List Micro USB — Vireless Receiver 1 CD 1 Operation Manual 1 Charge station — Environmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52	Working Voltage	DC5V
Standby Current 45ma Sleeping Current ≤ 2ua Accessory List Data Cable Micro USB Wireless Receiver 1 CD 1 Operation Manual 1 Charge station Environmental Parameter Storage Temperature -40°C ~ 60°C Vorking Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52	Max.Current	
Standby Current 45ma Sleeping Current ≤ 2ua Charging Current 450ma Accessory List Data Cable		
Accessory List	Standby Current	
Accessory List Micro USB	Charging Current	
Micro USB		Accessory List
Nireless Receiver	Data Cable	Micro USB
CD		
Departion Manual		
Charge station — Environmental Parameter Storage Temperature -40°C ~ 60°C Vorking Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification		
Environmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification	Charge station	
Storage Temperature -40 °C ~ 60 °C Working Temperature 0 °C ~ 50 °C Relative Humidity 0 ~ 95 % Height Range 1.5 M P Rating IP52 Certification		
Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification	Storage Temperature	-40°C ~ 60°C
Height Range 1.5M P Rating IP52 Certification	Working Temperature	
P Rating IP52 Certification		0 ~ 95%
Certification		
		1.5M
OF DOLOTER FACE AND LANCE FOR A STATE OF THE	IP Rating	1.5M IP52

welcome to contact with us.