



## Description

O scanner de mão Yumite inovador da fabricante do scanner de código de barras yumite proporciona características de desempenho a um preço acessível para tomar sua decisão de compra mais fácil do que nunca.

Se você está procurando a proteção do investimento e de grande valor em um pequeno scanner, luz que garante o máximo de produtividade, em seguida, o scanner de código de barras a laser YT-760A 1D é o scanner ideal para você. Na linha de check-out para o quarto dos fundos, o YT-760B ajuda você a tirar o máximo partido da sua solução específica do aplicativo em uma variedade de maneiras.



## Specification

Para	Model	YT-760A
<b>Image</b>		
Image		
<b>Performance Parameter</b>		
Depth Filed		
Wireless Transmitting Distance (without barrier)	---	
Infrared induction Distance	150 - 200mm	
Optical Source	650nm Visible red light diode	
Reading Percision	≥4mil	
Minimum Contrast	≥ 30%	
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.	
Decoding Speed	100times/second	
Barcode Sensitivity	Tilt	±65°
	Rotate	±42°
	Deflection	±60°
Data Interface	RJ-45	
<b>Mechanical and Electric Parameter</b>		
Size(Length x Width x Height)	92.5×70×154.6 mm	
Weight	148g	
Indicator	Siren and LED light	
Battery Capacity	---	
Max.Power	500mw	
Working Voltage	DC5V	
Current	Max.Current	100ma
	Working Current	97ma
	Standby Current	77ma
	Sleeping Current	---
Charging Current	450ma	
<b>Accessory List</b>		
Data Cable	Mirco USB	
Wireless Receiver	---	
CD	---	
Operation Manual	1	
Charge Station	---	
Holder	1Set	
<b>Environmental Parameter</b>		
Storage Temperature	-40°C ~ 60°C	
Working Temperature	0°C ~ 50°C	
Relative Humidity	0 ~ 95%	
Heigth Range	1.5M	
IP Rating	IP52	
<b>Certification</b>		
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004		



# Application

