

Possui a precisão do compacto laser, ergonômico e design.this acessíveis Laser scanners de código de barras combinam alta performance, precisão e valor. Eles oferecem soluções best-in-class para o varejo, ponto de venda, Escritório, Light Industrial, Armazém, Bibliotecas, médico, escritório Legal, Governo, marketing e qualquer aplicação repetitiva onde o tempo ea precisão são factores essenciais para ajudar as empresas a otimizar seu fluxo de trabalho. O USB é compatível com MAC IOS e Windows.



## **Specification**

		YT-760			
		Image			
lmage		Yumke			
		Performance Parameter			
Depth Filed		20mm			
Wireless Transmitting Distance (without barrier)		0 <del>-11-</del> 3			
Infrared Induct	tion Distance	<u> </u>			
Optical Source	9	650nm Visible red light diode			
		≥4mil			
Reading Perci					
Reading Perci Minimun Contr Decoding Cap	rast	≥4mil ≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.			
Minimun Contr	rast acity ed	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second			
Minimun Control  Decoding Cap  Decoding Spe	acity ed Tilt	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65°			
Minimun Control  Decoding Cap  Decoding Sperits  Barcode	ed Tilt Rotate	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42°			
Minimun Control  Decoding Cap  Decoding Sperits  Barcode  Sensitivity	acity ed Tilt	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65°			
Minimun Control  Decoding Cap  Decoding Sperits  Barcode  Sensitivity	ed Tilt Rotate	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60°			
Minimun Control  Decoding Cap  Decoding Specarcode  Sensitivity  Data Cable	ed Tilt Rotate	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x	ed Tilt Rotate Deflection	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter			
Decoding Cap Decoding Special Service Sensitivity Data Cable Size(Length x Weight	ed Tilt Rotate Deflection	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm			
Decoding Cap  Decoding Spe Barcode Sensitivity Data Cable  Size(Length x Weight Indicator Battery Capac	ed Tilt Rotate Deflection Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac	ed Tilt Rotate Deflection Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac	ed Tilt Rotate Deflection Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V			
Decoding Cap  Decoding Spe Barcode Sensitivity Data Cable  Size(Length x Weight Indicator Battery Capac Max.Power Working Volta	ed Tilt Rotate Deflection  Width x Height)  ity  ge [Max.Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac	ed Tilt Rotate Deflection Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma ——			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma —— 450ma			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma —— 450ma Accessory List			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma —— 450ma			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma —— 450ma Accessory List			
Decoding Cap Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Steeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second			
Decoding Cap  Decoding Special Special Sensitivity  Data Cable  Size(Length x Weight Indicator Battery Capac Max.Power Working Volta  Current  Charging curred  Data Cable  Wireless Recector  CD  Operation Mar	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Standby Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma —— 450ma Accessory List			
Decoding Cap  Decoding Special Special Sensitivity  Data Cable  Size(Length x Weight Indicator Battery Capac Max.Power Working Volta  Current  Charging curred  Data Cable  Wireless Recector  CD  Operation Mar	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Standby Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light ——— 450mw DC5V 90ma 62ma 71ma ——— 450ma  Accessory List  Micro USB ————————————————————————————————————			
Decoding Cap  Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre Data Cable Wireless Rece CD Operation Mar Charge Station	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping Current ent  eiver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light  —— 450mw DC5V 90ma 62ma 71ma —— 450ma  Accessory List  Micro USB ——— ——— ————————————————————————————			
Decoding Cap  Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta  Current Charging curre Data Cable Wireless Rece CD Operation Mar Charge Statior Storage Temp	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Standby Current ent  erature perature	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma —— 450ma  Accessory List Micro USB —— —— —— —— —— —— —— —— ——— —————————			
Minimun Control Decoding Specific Specific Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humin	ed Tilt Rotate Deflection  Width x Height)  ity  ge   Max.Current Working Current Standby Current Sleeping Current ent  erature berature dity	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light ——— 450mw DC5V 90ma 62ma 71ma ——— 450ma  Accessory List  Micro USB ——— ————————————————————————————————			
Decoding Cap  Decoding Speed Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capace Max. Power Working Volta Current Charging curred Data Cable Wireless Recector Operation Marcharge Station Storage Temp Working Temp Relative Humin Height Range	ed Tilt Rotate Deflection  Width x Height)  ity  ge   Max.Current Working Current Standby Current Sleeping Current ent  erature berature dity	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma —— 450ma  Accessory List Micro USB ——  Environmental Parameter  -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% 1.5			
Decoding Cap  Decoding Spe Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta	ed Tilt Rotate Deflection  Width x Height)  ity  ge   Max.Current Working Current Standby Current Sleeping Current ent  erature berature dity	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvaririans,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  156×64×91 mm 108g Siren and LED light ————————————————————————————————————			







Marca: Yumite

Número modelo: YT-760

Produtos Status: Ações