sem fio Bluetooth leitor de código de barras a laser



O scanner de código de barras a laser Bluetooth é fácil para usar. Ele pode ser emparelhado com o dispositivo que está com bluetooth, não mais software.YT-890 ios de apoio, Mac, Android, smart phone, PDA e assim por diante.

Performance Parameter Performance Parameter	Para Model	YT-890
Performance Parameter Performance Parameter		Image
Pepth Filed September Pepth Pep	lmage	Kings Com a security
Without barrier 15 - 20M	Depth Filed	20mm EAN13(10mil,13bytes)250mm Coole39(10mil,6bytes) 260mm Coole39(15.6mil,6bytes) 350mm Coole128(10mil,6bytes) 270mm Coole128(15.6mil,6bytes) 330mm EAN13(15.6mil,13bytes) 360mm EAN13(15.6mil,13bytes) 360mm Coole128(15.6mil,13bytes) Coo
Infrared induction disrance Optical Source (acting Precision Decoding Precision Decoding Capacity Decoding Capacity Decoding Speed Decoding Speed Defice Interleaved 2 of 5, Inte	Wireless Transmitting Distance	15 - 20M
Decidical Source Seafung Precision ≥ 4mil 2 mil 2 m	· · · · · · · · · · · · · · · · · · ·	
Seading Precision 2 4mil 3 30%	Optical Source	650nm Visible red light diode
Contract	Reading Precision	
Secoding Speed 100time/second 10time/second 10time/sec	Minimum Contrast Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal
Tit	Decoding Speed	
Interest	Barcado Tilt	±65°
Defection Section Se	Sonsitivity	
Mechanical and Electric Performance	Deflection	100000000000000000000000000000000000000
Size Length x Width x Height 92.5×70×154.6 mm Veight	vata interiace	
Veight 168g	Size/Langth v M/:dth v Ll=:=L4	
Siren and LED light		
Statery Capacity G00mah		
Max. Power 350mw Vorking Voltage DC5V Vorking Voltage T0ma Working Current 45ma Standby Current 45ma Steeping Current 450ma Charging Current 450ma Charging Current 450ma Charging Current 450ma Charging Current 1 Charging Current 1 Charge Seceiver 1 Charge Station 1 Charge station 1 Charge Station 1 Charge Temperature -40°C ~ 60°C Correct Storage Temperature 0°C ~ 50°C Celetative Humidity 0 ~ 95% Leight Range 1.5M PRating PS2 PRAting PS2 PS2 PS3 PS4 PS4 PS5 PS6 PS6 PS6 PS6 PS6 PS6 PS6 PS6 PS7 PS6 PS7 PS6 PS7 PS6 PS7 PS6 PS8 PS6 PS8 PS6 PS8 PS6 PS8 PS6 PS8 PS6 PS8 PS6 PS6 PS6 PS7 PS6		
Vorking Voltage		V 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
Max.Current 70ma Working Current 66ma Standby Current 45ma Sleeping Current ≤ 2ua Accessory List Micro USB Joata Cable — Vireless Receiver 1 5D 1 Operation Manual 1 Charge station — Environmental Parameter Vorking Temperature -0°C ~ 50°C telative Humidity 0 ~ 95% leight Range 1.5M P Rating IP52		
Working Current Standby C		
Standby Current Sleeping Cu	Current Working Current	66ma
Accessory List	Standby Current	
Accessory List Micro USB		
Micro USB	onarging Current	
Vireless Receiver	2.4.0.11	
CD	Data Cable	
Department 1	Wireless Receiver	
Environmental Parameter Storage Temperature -40°C ~ 60°C Vorking Temperature 0°C ~ 50°C telative Humidity 0 ~ 95% leight Range 1.5M P Rating IP52	CD	
Environmental Parameter Storage Temperature -40°C ~ 60°C Vorking Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Releight Range 1.5M P Rating IP52	Operation Manual	1
Contrage Temperature	Charge station	Facility and Day 1
Vorking Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Relative Range 1.5M ☐ Rating IP52	Storago Tomporatura	
Relative Humidity 0 ~ 95% Relative Humidity 1.5M P Rating IP52		
leight Range 1.5M P Rating IP52		
P Rating IP52		
to the second se		
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004	CE	

