

pequeño tamaño usb cable de códigos de barras CCD module



Description

El motor de exploración CCD puede decodificar casi cualquier tipo de 1D (rayas) de código de barras en su proyecto usando este escáner de código de barras compacto adorable. Hemos visto todo por una pequeña luz, módulo de escáner de baja potencia que pueden ser fácilmente motor de escáner CCD integrated. This OEM puede integrar fácilmente en varios kioscos, máquinas de venta de entradas, cajero automático, PDA, etc. POS O conectar con Android / Iphone de escanear directamente.



Feature

El motor de exploración YT-M301 CCD es todo en un módulo de escáner que es el más simple que pudimos encontrar.

En el extremo es sólo un cable USB, conéctelo a cualquier computadora y empezar a decodificar en un segundo.

Este escáner QR soporta RS232 y USB conexión de interfaz. Más requisitos de interfaz son negociables.



Specification

Para	Model	YT-M301														
Image																
Image																
Performance Parameter																
Depth Filed	<table border="1"> <thead> <tr> <th>Barcode Type</th> <th>Scanning Distance</th> </tr> </thead> <tbody> <tr> <td>code39(10mil,6bytes)</td> <td>310mm</td> </tr> <tr> <td>code39(15.6mil,6bytes)</td> <td>420mm</td> </tr> <tr> <td>code128(10mil,6bytes)</td> <td>340mm</td> </tr> <tr> <td>code128(15.6mil,6bytes)</td> <td>450mm</td> </tr> <tr> <td>EAN13(10mil,13bytes)</td> <td>310mm</td> </tr> <tr> <td>EAN13(15.6mil,13bytes)</td> <td>430mm</td> </tr> </tbody> </table>		Barcode Type	Scanning Distance	code39(10mil,6bytes)	310mm	code39(15.6mil,6bytes)	420mm	code128(10mil,6bytes)	340mm	code128(15.6mil,6bytes)	450mm	EAN13(10mil,13bytes)	310mm	EAN13(15.6mil,13bytes)	430mm
Barcode Type	Scanning Distance															
code39(10mil,6bytes)	310mm															
code39(15.6mil,6bytes)	420mm															
code128(10mil,6bytes)	340mm															
code128(15.6mil,6bytes)	450mm															
EAN13(10mil,13bytes)	310mm															
EAN13(15.6mil,13bytes)	430mm															
Wireless Transmitting Distance (without barrier)	—															
Infrared induction distance	150 - 200mm															
Optical Source	620nm Visible red light diode															
Imaging Sensor	CCD															
Image Resolution	2500Pixel															
Reading Precision	≥ 5mil															
Minimum Contrast	≥ 30%															
Decoding Capacity	Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect.															
Decoding Speed	280times/second															
Barcode Sensitivity	Tilt	±55°														
	Rotate	±25°														
	Deflection	±75°														
Data Interface	micro usb															
Mechanical and Electrical Performance																
Size(Length x Width x Height)	50×37.3×21.7 mm															
Weight	27g															
Indicator	Siren and LED light															
Battery Capacity	—															
Max.Power	700mw															
Working Voltage	DC5V															
Current	Max.Current	140ma														
	Working Current	90ma														
	Standby Current	45ma														
	Sleeping Current	—														
Charging Current	—															
Accessory List																
Data Cable	Micro USB															
Wireless Receiver	—															
CD	—															
Operation Manual	1															
Charge Station	—															
Environmental Parameter																
Storage Temperature	-40°C ~ 60°C															
Working Temperature	0°C ~ 50°C															
Relative Humidity	0 ~ 95%															
Height Range	1.5M															
IP Rating	IP52															
Certification																
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004																



Factory



Bienvenido a contactar con nosotros!