

Infrared induction distance 150 - 200mm  
Optical Source 620nm Visible red light diode  
Imaging Sensor CMOS(Image)  
Resolution Ratio 752×480  
Image Resolution ≥ 5mil  
Reading Depth Code 39 40mm -280mm(10mil); 85mm~325mm(15mil)  
PDF417 60mm -225mm(10mil); 60mm~340mm(15mil)  
Data Matrix 20mm -155mm(10mil); 35mm~235mm(15mil)  
QR Code 35mm -150mm(10mil); 20mm~230mm(15mil)  
Minimum Contrast ≥ 30%  
Barcode Types 2D "PDF417, QR Code(Model 1/2),micro QR  
Data Matrix(ECC200, ECC000,050, 080, 100,140)."  
1D "Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14,  
ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5,  
Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey etc."  
Decoding Speed 300times/s  
Barcode Sensitivity Tilt ±55°  
Rotate ±360°  
Deflection ±55°  
Data Interface Port TTL or RS232  
three trigger mode 1.Auto-trigger 2.RS232 trigger 3. IO signal trigger  
Mechanical and Electric Performance  
Size(Length x Width x Height) 70.3×50×22.4 mm  
Weight 47g  
Indicator Siren and LED light  
Max.Power 1150mw  
Working Voltage DC5V  
Current Max.Curren 230ma  
Working Current 100ma  
Stand-by Current 50ma  
Accessory List  
Data line RS232(1.8M)  
2.54mm flex cable□1.2m□  
IO control cable  
Operation Manual one  
Environmental Parameter  
Storage Temperature -40°C ~ 60°C  
Working Temperature -25°C ~ 60°C  
Relative Humidity 0 ~ 95%  
Height Range 2m  
IP Rating IP52

Certificates:

CE,RoHS,EMC,LVD□ISO9001:2008□ISO14001:2004

**Yumite**



yumite.en.alibaba.com



**Yumite**



yumite.en.alibaba.com





**Yumite**

CE 

yumite.en.alibaba.com

---

**Yumite Direct factory**

