

Symbologies	1D□UPC-A□UPC-E□EAN-8□EAN-13□Code 128□ GS1-128□ Code 39□Code 93□Code 11□Interleaved 2 of 5□Matrix 2 of 5□Industrial 2 of 5□Strande 2 of 5, Codabar□NW-7□MSI Plessey□GS1 Databar(RSS)□China Post□etc. 2D: QR Code, Data Matrix□PDF417□Micro PDF 417, Aztec, etc.
-------------	---

#### Physical Parameter

Weight	≈167g□with cable□
Dimension	L150mm * W70mm * H95mm
Communication Mode	USB□wireless 2.4G
Interface Type	USB
Power Supply	DC 5V@180mA(work□)

#### Environmental

Operating temperature	0°C to 50°C
Storage temperature	-30°C to 60°C
Humidity	5% to 95%□non-condensing□
Drop Height	1.5m
Temp. Test	30 minutes for high Temp., 30 minutes for low Temp.,
High Temp.	60°C
Low Temp.	-20°C
Transport vibration Test	10H@125RPM

#### Accessories List

Cable	USB, connect the scanner to a host device and charging.
Receiver	Used to receive and transmit scanner data.

#### Depth of field

Barcode	Precision	near	far
Code 39	0.1mm(4mil)	10mm	50mm
Code 39	0.127mm(5mil)	5mm	80mm
Code 39	0.5mm(20mil)	25mm	230mm
Code 39	1mm(40mil)	90mm	380mm
EAN-13	0.33mm(13mil)	30mm	180mm
QR Code	20.0mil	10mm	10mm
Data Matrix	10mil	25mm	55mm
PDF 417	6.8mil	5mm	80mm

Test Condition□T=25°C□Illumination=200LUX□PCS=0.9

