



## Description

The innovative Yumite hand-held scanner from yumite barcode scanner manufacturer delivers performance features at an affordable price to make your buying decision easier than ever.

If you're seeking investment protection and great value in a small, light scanner that assures maximum productivity, then the YT-760A 1D laser barcode scanner is the ideal scanner for you. From the checkout line to the back room, the YT-760B helps you make the most of your application-specific solution in a variety of ways.



## Specification

| Para   | Model  | YT-760A |
|--|--|---------|
| <b>Image</b>                                     |  |         |
| Image  |   |         |
| <b>Performance Parameter</b>                     |  |         |
| Depth Filed                                      |    |         |
| Wireless Transmitting Distance (without barrier) | ---  |         |
| Infrared induction Distance                      | 150 - 200mm  |         |
| Optical Source                                   | 650nm Visible red light diode  |         |
| Reading Percision                                | ≥4mil  |         |
| Minimum Contrast                                 | ≥ 30%  |         |
| Decoding Capacity                                | UPC/EAN/JAN,UPC/EAN with supplementals,<br>UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII,<br>Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93,<br>Discrete 2 of 5 IATA,RSSvarians,Codabar,chinese 2 of 5,Interleaved 2/5,<br>Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal<br>service code ,ect. |         |
| Decoding Speed                                   | 100times/second  |         |
| Barcode Sensitivity                              | Tilt   | ±65°    |
|  | Rotate   | ±42°    |
|  | Deflection   | ±60°    |
| Data Interface                                   | RJ-45  |         |
| <b>Mechanical and Electric Parameter</b>         |  |         |
| Size(Length x Width x Height)                    | 92.5×70×154.6 mm   |         |
| Weight   | 148g   |         |
| Indicator  | Siren and LED light  |         |
| Battery Capacity                                 | ---  |         |
| Max.Power  | 500mw  |         |
| Working Voltage                                  | DC5V   |         |
| Current  | Max.Current  | 100ma   |
|  | Working Current  | 97ma    |
|  | Standby Current  | 77ma    |
|  | Sleeping Current   | ---     |
| Charging Current                                 | 450ma  |         |
| <b>Accessory List</b>                            |  |         |
| Data Cable                                       | Mirco USB  |         |
| Wireless Receiver                                | ---  |         |
| CD   | ---  |         |
| Operation Manual                                 | 1  |         |
| Charge Station                                   | ---  |         |
| Holder   | 1Set   |         |
| <b>Environmental Parameter</b>                   |  |         |
| Storage Temperature                              | -40°C ~ 60°C   |         |
| Working Temperature                              | 0°C ~ 50°C   |         |
| Relative Humidity                                | 0 ~ 95%  |         |
| Heigth Range                                     | 1.5M   |         |
| IP Rating  | IP52   |         |
| <b>Certification</b>                             |  |         |
| CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004      |  |         |



# Application

