

small size wired usb ccd barcode module



Description

The CCD scan engine can decode nearly any kinds of 1D (striped) barcode in your project using this adorable compact barcode scanner. We've looked all over for a small, light, lowpower scanner module that can be easily integrated. This OEM ccd scanner engine can easily be integrated into various Kiosks, ticketing machines, ATM, PDA, POS etc. Or connect with Android/ Iphone to scan directly.



Feature

The YT-M301 CCD scan engine is all in one scanner module which is the simplest we could find.

On the end is just a USB cable, plug it into any computer and start to decode within one second.

This QR scanner supports RS232 and USB interface socket. More interface requirements are negotiable.



Specification

Para	Model	YT-M301
Image		
Image		
Performance Parameter		
Depth Filed		
Wireless Transmitting Distance (without barrier)	—	
Infrared induction distance	150 - 200mm	
Optical Source	620nm Visible red light diode	
Imaging Sensor	CCD	
Image Resolution	2500Pixel	
Reading Precision	≥ 5mil	
Minimum Contrast	≥ 30%	
Decoding Capacity	Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect.	
Decoding Speed	280times/second	
Barcode Sensitivity	Tilt	±55°
	Rotate	±25°
	Deflection	±75°
Data Interface	micro usb	
Mechanical and Electrical Performance		
Size(Length x Width x Height)	50×37.3×21.7 mm	
Weight	27g	
Indicator	Siren and LED light	
Battery Capacity	—	
Max.Power	700mw	
Working Voltage	DC5V	
Current	Max.Current	140ma
	Working Current	90ma
	Standby Current	45ma
	Sleeping Current	—
Charging Current	—	
Accessory List		
Data Cable	Micro USB	
Wireless Receiver	—	
CD	—	
Operation Manual	1	
Charge Station	—	
Environmental Parameter		
Storage Temperature	-40°C ~ 60°C	
Working Temperature	0°C ~ 50°C	
Relative Humidity	0 ~ 95%	
Height Range	1.5M	
IP Rating	IP52	
Certification		
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004		



Factory



welcome to contact with us!